



## TILE & FLOOR CARE TILE FLEX

### Description:

Tile & Floor Care Tile Flex is a ready mix acrylic adhesive that has many uses. Tile Flex's high strength thin bed adhesion may be used for sticking tiles to walls and floors onto substrates like plaster, primed/painted wood and board, dry walling, asbestos, metal etc. Tile Flex's quick cure formula allows for quick fixing in almost any situation. Tile Flex may be used in "wet use" areas providing it is primed with Tile and Floor Care Plaster Sealer. Tile and Floor Care Tile Flex may be used interior and exterior.

Tile and Floor Care Tile Flex will stick to ceramics and porcelain to plaster, primed/painted wood and board, dry walling, asbestos, metal. Tile and Floor Care Tile Flex may be used for sticking skirting's, dado rails, worktops, plasterboard, carpets, cover strips, plaster, primed/painted wood and board, dry walling, asbestos, metal, ceramics, brick, concrete and cork.

Available in 2 Kg & 5 Kg

Tile and Floor Care Tile Flex spreads at a rate of 1m<sup>2</sup> per 1 KG. Only spread as much adhesive as you intend to work with in a 5min to 10 minute period

### Tips & Tricks:

- Never butt join tiles.
- Allow for expansion joints every 2 to 3 meters in all directions on metal and wood substrates.
- Allow for expansion joints every 5 meters in all directions on concrete substrates.
- Ensure grout joints are a minimum of 2mm on walls and 3mm on floors.
- Apply tiles within 10 minutes after laying the bed of adhesive.
- Clean excess adhesive from exposed surfaces immediately. Do not allow to dry on surface.
- Do not add water or any other additives.
- Cement and plaster must be at least 14 days old before application.
- Concrete screeds must be at least 28 days old before application.
- Prime designated 'wet area' surfaces with Plaster Sealer.

### Directions – Tile Application:

Ensure all surfaces are clean and free from all dirt, oil, dust, wax and other contaminants. Clean with the correct Tile & Floor Care detergent if necessary. Phone TFC for directions if you are uncertain as to the correct application.

1. Using a notched applicator or trowel with 6mm teeth, spread adhesive to an even 3mm bed. Spread only as much adhesive as you need to work within 10 minutes.
2. Push the tile into the bed ensuring full contact between the tile and the adhesive.
3. When fixing heavy items or when dealing with uneven surfaces – use temporary support until the adhesive cures ( $\pm$  18 hours).
4. Clean excess adhesive from surfaces immediately and as you go. Do not allow it to dry on the surface.

**DO NOT** dilute in any way.

**DO NOT** dispose of this product down drains for risk of blockage.

**DO NOT** apply in temperatures below 10 degrees Celsius.

Shelf Life – Tile Flex has a shelf life of 6 months from date of packaging.